

**TAMRON**

Focus on the Future



Focal Length: 500mm Exposure: F6.7 1/250sec ISO: 1600

# 150-500<sub>mm</sub> F/5-6.7 Di III VC VXD

for Sony E, FUJIFILM X, and Nikon Z Mirrorless

**Unprecedented ultra-telephoto 500mm zoom  
sets your creative vision free**

Dramatically capture distant subjects.

VC and fast AF ensure you'll never miss a magnificent moment.

**Zoom in on the image of your dreams**



**150-500mm F/5-6.7 Di III VC VXD (Model A057)**

For Sony E-mount, FUJIFILM X-Mount, and Nikon Z mount  
Di III: For mirrorless interchangeable-lens cameras

# Ultra-telephoto zoom with comfortable, intuitive operation

Uncompromised pursuit of high optical performance in a compact body



Focal Length: 500mm Exposure: F6.7 1/1000sec ISO: 400

The 150-500mm F/5-6.7 Di III VC VXD (Model A057) features a very compact design, high image quality. This amazing zoom lens achieves a 500mm focal length while retaining a compact size, with a length of just 209.6mm (8.3 in) and a maximum diameter of 93mm, and is equipped with VC (Vibration Compensation), so it's easy to carry and comfortable to shoot handheld. The design places major emphasis on image quality. The optical construction features 25 elements in 16 groups and utilizes special lens elements and hybrid aspherical lens elements to control chromatic aberrations. BBAR-G2<sup>1</sup> Coating is used to suppress ghosting and flare, which could otherwise occur under backlit conditions. Additionally, the lens has a MOD (Minimum Object Distance) of 0.6m (23.6 in) at the 150mm end, so you can freely enjoy telephoto macro shooting of subjects at closeup distances. The 150-500mm F5-6.7 is a highly versatile lens that lets you capture a wide array of subjects ranging from landscapes and birds to sports and wildlife. You'll be thoroughly amazed when you experience the powerful and unique world of ultra-telephoto lenses for yourself.



Focal Length: 150mm Exposure: F8 1/100sec ISO: 400

# High-speed, high-precision AF means you'll never miss a photo opportunity



Focal Length: 150mm Exposure: F5.6 1/2000sec ISO: 500



VXD(Voice-coil eXtreme-torque Drive): linear motor focus mechanism

The 150-500mm F5-6.7 zoom's AF drive system is equipped with the VXD<sup>2</sup> linear motor focus mechanism. The VXD mechanism delivers extreme high-speed and high-precision movement and ensures exceptionally responsive performance when photographing subjects such as wild birds, sports, vehicles, and wildlife in general. The linear motor also suppresses drive noise and vibrations during focusing, making it ideal for shooting both still photos and video in environments that demand quietness.

# VC image stabilization facilitates shooting handheld at the ultra-telephoto position

When shooting in the ultra-telephoto range, even the smallest vibrations can lead to loss of image clarity. The 150-500mm F5-6.7 is equipped with VC functionality to support sharp images despite unavoidable camera shake. VC delivers powerful support for handheld shooting of scenes with low light levels, such as at evening and indoor, without the use of a tripod. The lens also features a VC mode selection switch with three modes including a dedicated panning mode, thereby enabling selection of the ideal VC mode to match shooting conditions and preferences.



Focal Length: 150mm Exposure: F6.3 1/1000sec ISO: 6400

## Additional features for greater convenience

- Arca-Swiss compatible tripod mount with strap attachment holes included
- FLEX ZOOM LOCK mechanism
- New switch design for improved operability
- Lens hood with flexible, protective front portion
- Moisture-Resistant Construction
- Fluorine Coating

## Built with Mirrorless in Mind

TAMRON's new 150-500mm F5-6.7 is compatible with many of the advanced features that are specific to mirrorless cameras. These include:

- Fast Hybrid AF
- Eye AF
- Direct Manual Focus (DMF)
- In-camera lens correction (shading, chromatic aberration, distortion)
- Camera-based lens unit firmware updates

\* Features vary by camera. Please consult your camera's instruction manual for details.

1 Broad-Band Anti-Reflection Generation 2 2 Voice-coil eXtreme-torque Drive

## 150-500mm F/5-6.7 Di III VC VXD (Model A057)

Model .....	A057	MOD.....	0.6m (23.6 in) (WIDE)/ 1.8m (70.9 in) (TELE)	Weight.....	1,725g (60.8 oz) (without tripod mount included)/ tripod mount 155g (5.5 oz)
Focal Length.....	150-500mm	Max. Mag. Ratio .....	1:3.1 (WIDE) / 1:3.7 (TELE)	Aperture Blades .....	7 (circular diaphragm)**
Max. Aperture.....	F5-6.7	Filter Size .....	φ82mm	Min. Aperture .....	F22-32
Angle of View (diagonal).....	16°25' - 4°57'	Max. Diameter .....	φ93mm	Standard Accessories.....	Round-shaped hood, Lens caps, Tripod mount
Optical Construction.....	25 elements in 16 groups	Length* .....	209.6mm (8.3 in)	Compatible Mounts .....	Sony E, FUJIFILM X and Nikon Z Mounts

\* Length is the distance from the front tip of the lens to the lens mount face.

\*\* The circular diaphragm stays almost perfectly circular up to two stops down from maximum aperture.

Specifications, appearance, functionality, etc. are subject to change without prior notice.

This product is developed, manufactured and sold under the license agreements with Sony, FUJIFILM and Nikon Corporations.

**Caution:** Please read the instruction manual carefully before using the lens.

## TAMRON AMERICAS

10 Austin Blvd., Commack, NY 11725  
Tel.: 631-858-8400  
Email: custserv@tamron.com



### Management on Quality and Environment

Tamron is certified with international standards: ISO 9001 for quality and ISO14001 for environmental management at its headquarters, domestic sales offices, China plant as well as production facilities in Aomori, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations.

www.tamron-americas.com

Note: Information valid as of August, 2023. Information in this publication is subject to change at any time without prior notice.